
# **SMD ONE PORT 915 MHz SAW RESONATOR**

ASR915E





#### > STANDARD SPECIFICATIONS:

Data measured with Source Impedance Zs= $50\Omega$ Load Impedance ZL= $50\Omega$  TA= $25^{\circ}$ C

	Load Impedal	ice ZL-:	3022	1A-23 C		
Item			Units	Minimum	Typical	Maximum
Center Frequency Fo			MHz	914.85	915.000	915.15
Insertion Attenuation @ 915MHz			dB	-	1.5	2.5
Quality Factor	Unloaded				0.0008	
	<b>50</b> $\Omega$ loaded		_ 		1300.0	
Temperature Stability	Turnover Temperature		°C		25.0	
	Turnover Frequency		KHz		Fo	
	Freq. Temp. Coefficient		ppm/°C <sup>2</sup>		0.032	
Frequency Aging			ppm/year		±10	
DC Insulation Resistance			$M\Omega$	1		
RF Equivalent RLC Model	Motional Resistance R <sub>1</sub>		Ω		18.0	
	Motional Inductance L₁		μH		25.2	
	Motional Capacitance C <sub>1</sub>		fF	-	1.2	
	Shunt Capacitance C <sub>0</sub>		pF		1.6	
Operating temp.		°C	-40°C to +85°C			
Storage temp.		°C	-45°C to +85°C			
Max. Rating	DC voltage	V	±10			
RF Power Dissipation		dBm	0			

#### > FREQUENCY RESPONSE:



#### > TEST CIRCUIT:




## > MARKING:

- 915R (9°

(915 Frequency in MHz) (ZY: Date code Z for month from A to L; Y for year, I.e. 4 for 2004 X: Traceability code)

PIN NO.	CONNECTIONS		
1	Input GND		
2	Input		
5	Output GND		
6	Output		
3,7	To be GNDed		
4,8	Case GND		

### OUTLINE DRAWING:



**ATTENTION:** Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

