


GNSS L1/L2/L5 Ceramic Patch Antenna



AANI-PP-0229

Request Samples



Check Inventory



25.0 x 25.0 x 8.0 mm

RoHS Compliant

MSL Level = N/A


Features

- Multiband Multi-Constellations GNSS Support
 - GPS: L1/L2/L5
 - Galileo: E1/E5a
 - Beidou: B1C/B2a
 - QZSS: L1/L2/L5
 - SBAS: L1/L5
 - IRNSS: L5
- Size: 25.0 x 25.0 x 8.0 mm
- Peak Gain: 5.0 dBic (L1), 1.2 dBic (L2), 1.0 dBic (L5)
- High Efficiency: 89% (L1), 74% (L2), 69% (L5)
- Light Weight: 17.12g


Applications

- GNSS Modules
- UAVs and Drones
- Asset Tracking & Telematics
- Intelligent Transportation
- Precision Agriculture
- Geolocation and Tracking

Product Image



GNSS L1/L2/L5 Ceramic Patch Antenna



AANI-PP-0229

Request Samples



Check Inventory




25.0 x 25.0 x 8.0 mm

RoHS Compliant

MSL Level = N/A

GNSS Frequency Bands Covered

GPS	L1 1575.42MHz	L2 1227.6MHz	L5 1176.45MHz	
	■	■	■	
GLONASS	G1 1598.06-1609.31MHz	G2 1242.93-1251.68MHz	G3 1202.025MHz	
	□	□	□	
Galileo	E1 1575.42MHz	E5a 1176.45MHz	E5b 1201.5MHz	E6 1278.75MHz
	■	■	□	□
BeiDou	B1I 1561MHz	B1c 1575.42MHz	B2a/B2I 1176.45MHz	
	□	■	■	
QZSS	L1 1575.42MHz	L2 1227.6MHz	L5 1176.45MHz	L6 1278.75MHz
	■	■	■	□
IRNSS/NAVIC			L5 1176.45MHz	
			■	
SBAS	L1/E1/B1 1575.42MHz		L5/B2a/E5a 1176.45MHz	
	■		■	



Frequency allocation: GNSS systems, upper L bands and lower L bands




12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-06-25

ABRACON IS
ISO9001-2015
CERTIFIED

GNSS L1/L2/L5 Ceramic Patch Antenna



AANI-PP-0229

Request Samples



Check Inventory



25.0 x 25.0 x 8.0 mm

RoHS Compliant

MSL Level = N/A

Electrical Specification

Parameters	Typ.			Units	Note
Frequency	1176.45 (L5)	1227.6 (L2)	1575.42 (L1)	MHz	
VSWR	< 2.0			:1	
Peak Gain	1.0	1.2	5.0	dBic	
Average Gain	-4.5	-2.3	-1.3	dBic	
Maximum Efficiency	69	74	89	%	
Average Efficiency	40	42	81	%	
Polarization	RHCP			-	
Nominal Impedance	50			Ω	

Note: All measurements were performed using the evaluation board in a free-space environment. Actual performance may vary depending on factors such as the ground plane, specific application, and surrounding environment.

Mechanical Specification

Parameter	Specification
Antenna Dimension	25.0 x 25.0 x 8.0 mm
Evaluation Board Dimension	70 x 70 mm
Mounting Type	Through Hole & Adhesive
Mounting Location	PCB Center Mounting
Material(s)	Ceramic
Weight	17.12 g

Environmental Specification

Parameter	Specification
Operating Temperature	-40°C to +85°C
Storage Temperature	-40°C to +85°C
RoHS Compliance	Yes




12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-06-25

ABRACON IS
ISO9001-2015
CERTIFIED

GNSS L1/L2/L5 Ceramic Patch Antenna



AANI-PP-0229

Request Samples



Check Inventory



25.0 x 25.0 x 8.0 mm

RoHS Compliant

MSL Level = N/A

Ordering Information

Part Number	Description
AANI-PP-0229	GNSS L1/L2/L5 Ceramic Patch Antenna




12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-06-25

ABRACON IS
ISO9001-2015
CERTIFIED

GNSS L1/L2/L5 Ceramic Patch Antenna



AANI-PP-0229

Request Samples



Check Inventory




25.0 x 25.0 x 8.0 mm


RoHS Compliant

MSL Level = N/A


Product Dimensions




TOP VIEW



FRONT VIEW



BOTTOM VIEW




Unit: mm



12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-06-25

ABRACON IS
ISO9001-2015
CERTIFIED



AANI-PP-0229

Request Samples



Check Inventory




25.0 x 25.0 x 8.0 mm

RoHS Compliant


MSL Level = N/A

Antenna Footprint & PCB Layout Guide

Top



Bottom




Unit: mm

Note: Antenna welding does not support reflow soldering, please use manual soldering, the recommended soldering time is $\leq 3s$, and the temperature is $390 \pm 20^{\circ}C$.

Transmission Line

The transmission line should be kept as short as possible and be designed to have a characteristic impedance of 50Ω. Abracon recommends using a Co-Planar Waveguide with Ground (CPWG), which dimensions can be derived by any trusted calculator, using the correct input for PCB materials and layer stack-up.

GNSS L1/L2/L5 Ceramic Patch Antenna



AANI-PP-0229

Request Samples



Check Inventory




25.0 x 25.0 x 8.0 mm


RoHS Compliant

MSL Level = N/A


Integration Guide




Top with Antenna



Top without Antenna



Bottom with Connector



Bottom without Connector

Unit: mm

The transmission line of the antenna is shown below the bottom image.




12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-06-25

ABRACON IS
ISO9001-2015
CERTIFIED

GNSS L1/L2/L5 Ceramic Patch Antenna



AANI-PP-0229

Request Samples



Check Inventory





25.0 x 25.0 x 8.0 mm

RoHS Compliant

MSL Level = N/A

Measurement Setup





AANI-PP-0229

Request Samples



Check Inventory






25.0 x 25.0 x 8.0 mm

RoHS Compliant

MSL Level = N/A

Reflection Characteristics – Return Loss & VSWR





AANI-PP-0229

Request Samples



Check Inventory






25.0 x 25.0 x 8.0 mm

RoHS Compliant

MSL Level = N/A

Radiation Characteristics – Gain





AANI-PP-0229

Request Samples



Check Inventory




25.0 x 25.0 x 8.0 mm


RoHS Compliant

MSL Level = N/A

Radiation Characteristics – Total Efficiency (%)



GNSS L1/L2/L5 Ceramic Patch Antenna



AANI-PP-0229

Request Samples



Check Inventory








25.0 x 25.0 x 8.0 mm

RoHS Compliant

MSL Level = N/A

Radiation Characteristics – 3D & 2D Pattern

1176MHz




12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-06-25

ABRACON IS
ISO9001-2015
CERTIFIED

GNSS L1/L2/L5 Ceramic Patch Antenna



AANI-PP-0229

Request Samples



Check Inventory





25.0 x 25.0 x 8.0 mm


RoHS Compliant

MSL Level = N/A


1227MHz




XY plane



XZ plane



YZ plane




12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-06-25

ABRACON IS
ISO9001-2015
CERTIFIED

GNSS L1/L2/L5 Ceramic Patch Antenna



AANI-PP-0229

Request Samples



Check Inventory








25.0 x 25.0 x 8.0 mm

RoHS Compliant

MSL Level = N/A

1575MHz




12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-06-25

ABRACON IS
ISO9001-2015
CERTIFIED

GNSS L1/L2/L5 Ceramic Patch Antenna



AANI-PP-0229

Request Samples



Check Inventory



25.0 x 25.0 x 8.0 mm

RoHS Compliant

MSL Level = N/A

Packaging

50 pcs per tray

300 pcs per inner box

600 pcs per carton

ATTENTION: Abracon LLC's products are Commercial-Off-The-Shelf ("COTS"), which are designed, intended, and validated for use in commercial, industrial, and automotive applications. The customer is responsible for testing and verifying the performance of an Abracon solution to meet their system-level requirements.



12117 Bee Caves Rd, Bldg-3, Suite 200 Bee
Cave, TX 78738
Phone: 512-371-6159 | Fax: 512-351-8858
For terms and conditions of sales, please visit:
www.abracon.com

REVISED: 08-06-25

ABRACON IS
ISO9001-2015
CERTIFIED