

Package	Description
7 x 5 mm SMD Ceramic	Ultra Low Jitter 1pS

Features

- Ultra low Jitter at 1pS
- Low Power Consumption
- Standby function
- Tape and Reel
- Miniature profile
- 3.3V or 5.0V optional




Electrical Characteristics

Parameter	Conditions	Characteristics		Units
Output Logic	-	HCMOS / TTL Output		-
Input Voltage (VDD)	-	3.3±10%	5.0±10%	VDC
Frequency Range (fO)	-	1.544~133.333		MHz
Operating Temperature (TOPR)	-	0 ~ +70 (Std.) / -40 ~ 85 (Option)		°C
Storage Temperature (TSTG)	T _{STG}	-55 ~ +125		°C
Frequency Stability	a + b + c + d	±25, ±50, ±100 max.		PPM
	(a) Frequency Tolerance	Inclusive of Overall Stability		-
	(b) Temperature Stability	Inclusive of Overall Stability (Operating Temperature)		-
	(c) Input Voltage Stability	Inclusive of Overall Stability (VDD ±10%)		-
	(d) Load Stability	Inclusive of Overall Stability (RL ±5%)		-
Input Current (IDD)	-	12 ~ 60 max.	25 ~ 100 max.	mA
Aging	@ 25°C	±5 max.		PPM/Y
Rise Time (TR) / Fall Time (TF)	-	8 max. (0.4V to 2.4V w/ TTL, 20% ~ 80% / HCMOS)		nS
PIN 1 Tri-State	-	Option		-
Output Voltage High "1" VOH	TTL Load	2.4 min		VDC
	HCMOS Load	2.7 min.	VDD-0.5 min.	
Output Voltage Low "0" VOL	TTL Load	0.4 max.		VDC
	HCMOS Load	0.5 max.		
Duty Cycle	-	50 ±10 (Std.) / 50 ±5 (Option)		%
Start-Up Time (TS)	1~ 35 MHz	4 max.		mS
	35 ~ 125.000 MHz	10 max.		
Jitter	(Bandwidth 12Khz ~ 20Mhz)	±1		ps RMS

Part Numbering Guide


Series Number	Frequency	Voltage Supply Option	Frequency Tolerance & Stability (max.)	Operating Temp. (°C)	Duty Cycle	Pin 1 Connection
433	- 24.0M	- 3	E	N	- T	TS
Oscilent SMD Oscillators	Enter your desired frequency e.g. 24.0M = 24.000MHz	5 = 5VDC 3 = 3.3VDC	D = ±100 PPM E = ±50 PPM F = ±25 PPM G = ±20 PPM J = ±15 PPM	Blank* = 0~+70 C = -10~+70 D = -20~+70 N = -40~+85	Blank* = 50±10% T = -50±5%	NC = No Connection TS = Tri-State Enable High
<p>NOTE: - Deviations on all parameters available. Please consult Oscilent for details.</p> <p>*STANDARDS: - "Blank" part number selections, indicate standard variables for the particular characteristic.</p> <p>PACKAGING: - Add -TR for Tape/Reel.</p>						

Package Dimensions



PIN	
1	No Connection or Tri-State Enable High
2	Case Ground
3	Output
4	VDD

Suggest Solder Pad Layout



All Dimensions in millimeters

Tape & Reel

- 1000 pieces per reel
- Compliant to EIA-481
- All Dimensions in Millimeters

