

CHIP INDUCTORS (ASMPH AND ASMCI)

Compact chip inductors support -40°C to 85°C temperature range



SERIES	INDUCTOR TYPE	INDUCTANCE RANGE (μH)	CURRENT RATING RANGE (mA)	DCR RANGE (Ohms)	SMALLEST FOOTPRINT AVAILABLE (mm)	APPLICATION
ASMPH-0603	Chip	0.22 to 2.2	300 to 1250	0.1 to 0.3	1.6 x 0.8 x 0.8	IoT Wearables Portable and battery operated Industrial Consumer Point-of-load
ASMPH-0805	Chip	0.47 to 4.7	280 to 1200	0.08 to 0.25	2.0 x 1.25 x 0.9	
ASMPH-0806	Chip	0.47 to 4.7	220 to 1500	0.08 to 0.14	2.0 x 1.6 x 0.9	
ASMPH-1008	Chip	0.47 to 4.7	320 to 1500	0.04 to 0.11	2.5 x 2.0 x 0.9	
ASMCI-0603	Power	0.1 to 10	50 to 700	0.14 to 0.9	1.6 x 0.8 x 0.8	
ASMCI-0805	Power	0.1 to 10	60 to 1000	0.07 to 0.5	2.0 x 1.25 x 1.25	

LOW PROFILE SMD SHIELDED INDUCTORS

ASPI series inductors are designed for medium to high power applications requiring high inductance and compact form factors. These inductors tolerate high operating temperatures including self heating.



SERIES	SIZE / DIMENSION (mm)	HEIGHT (mm)						@10 μH		OPERATING TEMPERATURE (°C)	APPLICATIONS	
			0.1	1	10	100	1000	IRATED (A)	DCR (Ω)			
ASPI-2010	2.00 x 1.60	1.00	0.47		10				0.56	0.712	-40 to 125	Industrial Instrumentation Computing/ servers Medical Lighting Portable/battery powered Point-of-load
ASPI-2510	2.50 x 2.00	1.00	6.80		10			0.75	0.445	-25 to 120		
ASPI-2515	2.50 x 2.00	1.50	0.47		10			0.80	0.220	-25 to 120		
ASPI-0309	3.00 x 3.00	0.90		2.20		47		0.43	0.640	-30 to 100		
ASPI-0315FS	3.00 x 3.00	1.50	1.00			100		0.80	0.220	-25 to 120		
ASPI-0418FS	4.00 x 4.00	1.80	0.82			220		1.30	0.150	-25 to 120		
ASPI-4030S	4.00 x 4.00	3.00	0.91			120		1.50	0.100	-40 to 125		
ASPI-0428S	4.70 x 4.70	3.00		1.20		180		1.00	0.128	-40 to 95		
ASPI-0530LR	5.60 x 5.20	3.00		1.50		5.60		1.00	0.128	-40 to 95		
ASPI-0615FS	6.00 x 6.00	2.20	0.50			47		1.50	0.090	-25 to 120		
ASPI-6045S	6.00 x 6.00	4.50	0.82			330		2.45	0.048	-40 to 125		
ASPI-0403S	6.60 x 4.45	2.92		1.00		1000		1.00	0.075	-40 to 85		
ASPI-0630LR	7.20 x 6.65	3.00	0.47			22		4.00	0.068	-55 to 125		
ASPI-7318	7.30 x 6.80	3.00	0.10			22		3.00	0.105	-55 to 125		
ASPI-8040S	8.00 x 8.00	4.20	0.82			330		3.30	0.029	-40 to 125		
ASPI-104S	10.10 x 10.00	4.00		7.00		470		3.80	0.035	-40 to 85		
ASPI-1040HI	11.15 x 10.00	4.00	0.16			10		7.50	0.030	-55 to 125		
ASPI-1367	14.00 x 12.90	6.70	0.10			10		10.00	0.019	-40 to 125		
ASPI-1306T	18.54 x 15.24	7.11		1.00		1000		4.30	0.031	-40 to 85		

Applications:



Lighting



Solar / Micro-Inverter



Switch Mode Power Supplies



Motor Control




IoT



Wearables

HIGH POWER TOROID INDUCTORS BY ABRACON



ATCA toroid inductors utilizing high efficiency, powdered iron core are designed for high power applications where through-hole assembly technology is used. Unshielded, the toroidal form-factor inherently suppresses EMI. Supporting either vertical or horizontal orientations, these inductors can be placed in orthogonal orientation with respect to each other, further reducing coupling and crosstalk due to EMI. They support current rating up to 10A and extended operating temperature range of -40°C to 105°C.

PART NUMBER (NOT INCLUDING INDUCTANCE CODE)	INDUCTANCE RANGE (μH)	DCR RANGE (mΩ)	IDC RANGE (A)	APPLICATIONS
ATCA-01-XXXM	20-220	21-190	1.0-5.0	Industrial High power SMPS LED ballasts Lighting White goods Appliances High power passive filters
ATCA-02-XXXM	22-470	14-286	1.0-5.0	
ATCA-03-XXXM	25-230	16-159	1.0-5.0	
ATCA-04-XXXM	50-960	22-150	1.0-5.0	
ATCA-05-XXXM	90-1800	34-680	1.0-5.0	
ATCA-06-XXXM	820-780	33-342	1.0-5.0	
ATCA-07-XXXM	30-850	9-211	2.0-10.0	
ATCA-08-XXXM	75-680	14-105	5.0-10.0	

GENERAL INDUCTORS



SERIES	INDUCTOR TYPE	INDUCTANCE RANGE (μH)	CURRENT RATING RANGE (A)	DCR RANGE (Ohms)	SMALLEST FOOTPRINT AVAILABLE (mm)
AISM-1008	Molded Wire-Wound	0.01 to 100	0.06 to 0.55	0.26 to 21	2.5 x 2.0 x 1.8
AISM-1210	Molded Wire-Wound	0.01 to 330	0.04 to 0.45	0.13 to 34	3.2 x 2.5 x 2.2
AISM-1812	Molded Wire-Wound	0.1 to 820	0.03 to 0.80	0.2 to 43	4.8 x 3.5 x 3.5
AISM-1812H	Molded Wire-Wound	1 to 330	0.09 to 1.05	0.11 to 13	4.5 x 3.2 x 3.2
AISM-2220	Molded Wire-Wound	1 to 1000	0.085 to 1.8	0.03 to 15	5.8 x 5.2 x 5.2
AISC-1206H	Unshielded	45nH to 0.68mH	0.3 to 4.4	0.027 to 8.45	3.2 x 1.6 x 1.8
AISC-1210HS	Wire-Wound	2.2 to 33	0.22 to 0.8	1 to 5	3.2 x 3.05 x 1.3
AISC-1812H	Unshielded	1 to 2200	0.03 to 1.08	0.08 to 65	4.5 x 3.2 x 2.6
AISC-2220H	Unshielded	120nH to 10mH	0.05 to 6.0	0.01 to 140	5.7 x 5.0 x 4.7
AIRD	Drum Core	1μH to 19mH	0.5 to 27.0	0.002 to 0.7	21.0 x 16.5
AISR-01	Drum Core	1mH to 120mH	0.008 to 0.39	1.5 to 97	10.5 x 10.5
AISR-04	Drum Core	10 to 820	0.43 to 3.9	0.02 to 1.3	10.5 x 10.5
AISR-875	Drum Core	10μH to 10mH	0.084 to 2.9	0.05 to 33	7.5 x 7.8
AIUR	Drum Core	1μH to 68mH	0.02 to 95.0	0.012 to 80	7.5 x 8.5